Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-227-9234

view Online at https://aerobasegroup.com/nsn/5935-00-227-9234
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle shape w/cable clamp
Overall Diameter:
0.946 inches
Body Angle In Deg:
90.0
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
10sl-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
1.482 inches
Distance From Centerline To Cable End:
1.503 inches
Thready Qty Per Inch (tpi):
24

24

NSN 5935-00-227-9234 Electrical Plug Connector - Page 2 of 2



	inches
	inal Location:
	single mating end single contact grouping
	act Material:
	er alloy single mating end single contact grouping
	act Surface Treatment:
	single mating end single contact grouping
	Material:
	er synthetic single mating end
	inal Type:
	r well single mating end single contact grouping
	Material:
Alumii	num alloy
Shell	Surface Treatment:
Cadm	ium
Shell	Surface Treatment Specification:
Qq-p-	416, type 2, cl 3 federal specification single treatment response
Incluc	ded Contact Quantity:
3 sing	le mating end single contact grouping
Includ	ded Contact Type:
Round	d socket single mating end single contact grouping
Precie	ous Material And Location:
Conta	ct surfaces silver
Precie	ous Material And Weight:
0.003	silver grains, troy
Precie	ous Material:
Silver	
Threa	d Series Designator:
Unef	
Shelf	Life:
N/a	
Unit C	Of Measure:
Demil	litarization:
No	
Fiig:	
A039b	00