Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-228-8621

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
2.250 inches
Overall Height:
2.030 inches
Overall Width:
2.030 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.147 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.562 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
4
Thread Size:
1.750 inches
Terminal Location:
Back single mating and single contact grouping

Back single mating end single contact grouping



	tact Material:
	per alloy single mating end single contact grouping
	tact Surface Treatment:
	I single mating end single contact grouping
Inse	rt Material:
Plast	tic diallyl phthalate single mating end
Tern	ninal Type:
Crim	p single mating end single contact grouping
Shel	II Material:
Alum	ninum alloy
Shel	I Surface Treatment:
	mium
	rt Material Specification:
	n-19833, type gdi-30f military specification single material response single mating end
	uded Contact Quantity:
50 si	ingle mating end single contact grouping
Inclu	uded Contact Type:
Coax	xial socket single mating end single contact grouping
Prec	ious Material And Location:
Cont	act surfaces gold
Prec	ious Material And Weight:
	0 gold grains, troy
Prec	cious Material:
Gold	
	ad Series Designator:
Dout	ble stub
Shel	If Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	
A039	960
Mil-s	std (military Standard):
Mil-n	n-19833 spec.