Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-228-9360

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.880 inches
Overall Height:
0.620 inches
Overall Width:
0.210 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration proof
Distance Between Mounting Facility Centers:
0.656 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Length:
0.220 inches
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Ostalas configurations and signals as a test and signal

Solder well single mating end single contact grouping

NSN 5935-00-228-9360

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification: Mil-m-14 military specification single material response single mating end **Included Contact Quantity:** 9 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.009 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.