Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-228-9879

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
Between 1.471 inches and 1.601 inches	
Overall Height:	
Between 1.490 inches and 1.510 inches	
Overall Width:	
Between 1.490 inches and 1.510 inches	
Unthreaded Mounting Hole Diameter:	
Between 0.118 inches and 0.124 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 1.151 inches and 1.161 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 1.151 inches and 1.161 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.750 inches and 0.760 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
20-15 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
41.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Connector Locking Method:	
Externally threaded shell	



**Thread Length:** 0.625 inches **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 7 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end single contact grouping **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-r-3065 spec.