

View Online at <https://aerobasegroup.com/nsn/5935-00-229-7784>

Body Style:

Straight shape

Overall Length:

Between 2.713 inches and 2.745 inches

Overall Height:

0.664 inches

Overall Width:

Between 0.478 inches and 0.510 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.081 inches and 0.091 inches

Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"c, 27w2" single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.