## NSN 5935-00-229-7785

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-229-7785 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/flange **Overall Length:** Between 2.110 inches and 2.140 inches **Overall Height:** Between 1.980 inches and 2.020 inches **Overall Width:** Between 1.980 inches and 2.020 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.145 inches and 0.151 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.557 inches and 1.567 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.557 inches and 1.567 inches **Distance From Mounting Shoulder To Front Face:** Between 0.975 inches and 0.985 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 28-6 all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 80.0 all mating ends all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 900.0 all mating ends all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 all mating ends all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Shell Solid

## NSN 5935-00-229-7785

Connector Adapter - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings and silver all mating ends all contact groupings
Insert Material:
Rubber all mating ends
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
3 2nd mating end all contact groupings
Included Contact Type:
Round socket 2nd mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.030 gold grains, troy and 0.030 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
N/a
N/a
Unit Of Measure:
700300