NSN 5935-00-230-7678

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-230-7678

Body Style:
Straight type
Overall Length:
3.844 inches
Overall Height:
0.609 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Distance Between Mounting Facility Centers:
3.438 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
875.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate mineral filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping

NSN 5935-00-230-7678

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.