# NSN 5935-00-231-5529

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-231-5529

Thread Class:
2b and 2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.060 inches
Overall Height:
0.740 inches
Overall Width:
0.280 inches
Environmental Protection:
Salt water resistant and vibration resistant
Distance Between Mounting Facility Centers:
0.814 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1, over copper military specification single treatment response single mating end single contact grouping

**Terminal Type:**Crimp single mating end single contact grouping

# NSN 5935-00-231-5529

Electrical Receptacle Connector - Page 2 of 2



## **Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

# **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

# **Included Contact Quantity:**

20 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.020 gold grains, troy

#### **Precious Material:**

Gold

## **Thread Series Designator:**

Unc and unc and unc

#### Shelf Life:

N/a

#### **Unit Of Measure:**

#### **Demilitarization:**

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.