NSN 5935-00-231-8874

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-231-8874 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.531 inches **Overall Diameter:** 2.500 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Distance From Mounting Shoulder To Front Face:** 1.250 inches **Mounting Facility Thickness:** Between 0.094 inches and 0.329 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 32-17 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 135.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 18

Thread Size: 2.000 inches

NSN 5935-00-231-8874

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location: |
|--|
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Contact Surface Treatment Specification: |
| Qq-s-365 federal specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Included Contact Quantity: |
| 4 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.020 silver grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |