NSN 5935-00-232-3060

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-232-3060

Body Style: Straight shape **Overall Length:** Between 3.965 inches and 3.975 inches **Overall Height:** Between 0.995 inches and 1.005 inches Overall Width: 1.275 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.120 inches and 0.130 inches **Distance Between Mounting Facility Centers:** Between 3.622 inches and 3.628 inches **Mating End Quantity: Contact Position Arrangement Style:** 32 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Latch **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** Copper alloy

Nickel

Shell Surface Treatment:

NSN 5935-00-232-3060

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

32 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.032 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0