Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-1555

### Thread Class:

2b

**Thread Direction:** 

Right-hand

### Body Style:

Straight edge type w/mounting flange

#### **Overall Length:**

5.805 inches

#### **Overall Height:**

1.200 inches

#### **Overall Width:**

0.370 inches

### **Distance Between Mounting Facility Centers:**

5.545 inches

#### **Board Accommodated Length:**

5.125 inches single board

# Threaded Device Type:

Mounting hole

### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

### Mating End Quantity:

1

## Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

### Thread Size:

0.112 inches

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Wire wrap single mating end single contact grouping

## Insert Material Specification:

Mil-m-19833, type gdi30 military specification single material response single mating end



**Included Contact Quantity:** 80 single mating end single contact grouping Included Contact Type: Leaf spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.080 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.