NSN 5935-00-233-1765

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-1765

Body Style:
Angle shape, internal coupling
Overall Length:
1.752 inches
Overall Height:
1.530 inches
Overall Diameter:
1.510 inches
Environmental Protection:
Pressure proof and moisture resistant and shock resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
20-41 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
321.0
Shell Type:
Potting
Potting Connector Locking Method:
•
Connector Locking Method:
Connector Locking Method: Bayonet latch
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification: Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Potting type Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Contact Surface Treatment Specification: Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping Terminal Type:

NSN 5935-00-233-1765

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment: Cadmium and chromate **Included Contact Quantity:** 41 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.041 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.