

View Online at <https://aerobasegroup.com/nsn/5935-00-233-2477>

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 3.060 inches and 3.090 inches

Overall Height:

0.702 inches

Overall Width:

Between 0.325 inches and 0.335 inches

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.135 inches

Distance Between Mounting Facility Centers:

Between 2.770 inches and 2.780 inches

Board Accommodated Length:

2.300 inches single board and 2.315 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Fixed contact to contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c or d, class i military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.044 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.