

View Online at <https://aerobasegroup.com/nsn/5935-00-233-2723>

Body Style:

Straight shape

Overall Length:

Between 4.295 inches and 4.305 inches

Overall Height:

0.718 inches

Overall Width:

Between 0.355 inches and 0.365 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.117 inches

Distance Between Mounting Facility Centers:

Between 3.995 inches and 4.005 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

37 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Polarization Method:

Contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdi-5 military specification single material response single mating end

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.037 gold grains, troy and 0.037 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.