## NSN 5935-00-233-4404

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-4404

view Online at https://aerobasegroup.com/nsn/5935-00-233-4404
Body Style:
Straight type
Overall Length:
0.840 inches
Overall Width:
0.238 inches
Body Height:
0.320 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
3.0 single mating end all contact groupings
Terminal Location:
Side single mating end 4th contact grouping
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and nickel single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 2nd treatment response single mating end all contact groupings and qq-n-290 federal specification 1st
treatment response single mating end all contact groupings
Terminal Type:
Pin single mating end all contact groupings
Contact Material Specification:
Qq-b-750 federal specification single material response single mating end all contact groupings
Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

8 single mating end 1st contact grouping

#### **Included Contact Type:**

Flat socket single mating end all contact groupings

#### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.016 gold grains, troy

# NSN 5935-00-233-4404

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.