NSN 5935-00-233-4663

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-4663 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.232 inches **Overall Diameter:** 1.641 inches **Distance From Mounting Shoulder To Front Face:** Between 0.691 inches and 0.722 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 19p single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 315.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:**

19 single mating end single contact grouping

NSN 5935-00-233-4663

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.019 gold grains, troy Precious Material: Gold Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A039b0