Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-5430

Thread Class:
2a
Za Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.551 inches
Overall Height:
1.711 inches
Overall Width:
1.711 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.380 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.380 inches
Distance From Mounting Shoulder To Front Face:
0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
24-155 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
311.0 and 191.0 and 160.0 and 116.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
1.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Shell Material Specification:** Qq-a-325, comp 6061, grade t6 federal specification single material response **Included Contact Quantity:** 155 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.155 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unc **Specification Data:** 81349-mil-c-81511/21 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.