# NSN 5935-00-233-6062

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-6062 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.486 inches and 1.551 inches **Overall Height:** Between 1.695 inches and 1.711 inches **Overall Width:** Between 1.695 inches and 1.711 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.370 inches and 1.380 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.370 inches and 1.380 inches **Distance From Mounting Shoulder To Front Face:** Between 0.894 inches and 0.906 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 24-74 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 225.0 and 190.0 and 160.0 and 50.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thread Size: 1.500 inches

**Terminal Location:** 

Back single mating end single contact grouping

# NSN 5935-00-233-6062

Electrical Receptacle Connector - Page 2 of 2



_							
т-	Λn	+-	rt.	ΝЛ	210	eria	
•	VII	ιca	·ι	IVI	au	zı ıa	и.

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### **Shell Material:**

Aluminum alloy

### **Shell Surface Treatment:**

Cadmium

### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

### **Shell Material Specification:**

Qq-a-367, comp 6061 t6 federal specification single material response

## **Included Contact Quantity:**

74 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.074 gold grains, troy

# **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unc

## **Specification Data:**

81349-mil-c-81511/21 government specification

# Shelf Life:

N/a

### **Unit Of Measure:**

### **Demilitarization:**

No

## Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.