Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-6735

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Angle shape
Overall Length:
1.120 inches
Overall Height:
0.870 inches
Overall Width:
Between 0.365 inches and 0.395 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration proof
Cable Entrance Diameter:
0.110 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
40
Thread Size:
0.281 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Gold **Shell Material Specification:** Qq-b-626, comp 22, 1/2 h federal specification single material response **Insert Material Specification:** Mil-m-14077, class 1 military specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact and shell surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A039b0 Mil-std (military Standard): Mil-m-14077 spec.

N/a

No