## NSN 5935-00-233-6847

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-6847 **Thread Class:** ΑI **Body Style:** Straight shape **Overall Length:** Between 2.713 inches and 2.745 inches **Overall Height:** 0.661 inches **Overall Width:** Between 0.478 inches and 0.510 inches **Environmental Protection:** Heat resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 2.495 inches and 2.505 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** "c, 27w2" single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** 

Cadmium

# NSN 5935-00-233-6847

Electrical Receptacle Connector - Page 2 of 2



#### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

#### **Insert Material Specification:**

Mil-m-19833, type gdi-30f military specification single material response single mating end

#### **Included Contact Quantity:**

25 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.025 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-m-19833 spec.