Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-233-6933

Thread Class: 2b **Thread Direction: Right-hand Body Style:** Straight edge type w/mounting flange **Overall Length:** Between 3.640 inches and 3.680 inches **Overall Height:** 0.737 inches **Overall Width:** Between 0.320 inches and 0.360 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Mounting Facility Centers:** Between 3.401 inches and 3.411 inches **Board Accommodated Length:** 2.967 inches single board and 2.977 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches Mating End Quantity: **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:**

Tab, solder lug single mating end single contact grouping

1

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:	
Mil-m-19833, type gdi-30f military specification single material response single mating end	
Included Contact Quantity:	
18 single mating end single contact grouping	
Included Contact Type:	
Leaf spring single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold and contact surfaces silver	
Precious Material And Weight:	
0.018 gold grains, troy and 0.018 silver grains, troy	
Precious Material:	
Gold and silver	
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	