## NSN 5935-00-233-7042



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-233-7042 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/backshell **Overall Length:** 2.250 inches **Overall Diameter:** 2.063 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 142.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thready Qty Per Inch (tpi): 10 **Thread Size:** 1.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** 

Gold single mating end single contact grouping

Crimp single mating end single contact grouping

Plastic diallyl phthalate single mating end

**Insert Material:** 

**Terminal Type:** 

## **NSN 5935-00-233-7042**Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response single mating end
Included Contact Quantity:
42 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.042 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-19833 spec.