NSN 5935-00-234-0259

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-234-0259

| Thread Class: |
|---|
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Rectangular shape |
| Overall Length: |
| 3.060 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.782 inches |
| Overall Height: |
| 1.153 inches |
| Overall Width: |
| 0.500 inches |
| Environmental Protection: |
| Vibration resistant |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.250 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 100 single mating end |
| Polarization Method: |
| Jackscrew and guide pin/socket |
| Connector Locking Method: |
| Jackscrew-socket |
| Thread Length: |
| 0.350 inches |
| Thready Qty Per Inch (tpi): |
| 40 and 40 and 40 |
| Thread Size: |
| 0.112 inches and 0.112 inches and 0.112 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Insert Material Specification: |
| Mil-p-19833, ty gdi-30f military specification single material response or mil-m-14, ty sdg-f military specification single material response |
| single mating end |
| Unable To Decode: |
| Unable to decode and unable to decode |

Unable to decode and unable to decode

Unable To Decode:

NSN 5935-00-234-0259

Electrical Receptacle Connector Body - Page 2 of 2



Mil-std (military Standard):

Mil-p-19833 spec.