

View Online at <https://aerobasegroup.com/nsn/5935-00-234-5857>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

6.550 inches

**Overall Diameter:**

1.350 inches

**Cable Entrance Diameter:**

Between 0.375 inches and 0.625 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-1 single mating end

**Contact Removability:**

Nonremovable single mating end 2nd contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end 2nd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end 1st contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end 1st contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Thread Length:**

0.625 inches

**Thread Size:**

1.125 inches

**Terminal Location:**

Back all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Silver all mating ends all contact groupings

**Insert Material:**

Rubber all mating ends

**Terminal Type:**

Solder well all mating ends all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:**

6 single mating end 2nd contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0