## NSN 5935-00-234-6615

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-234-6615 **Thread Class:** 2b **Body Style:** Straight shape, external coupling **Environmental Protection:** Moisture resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-28 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 20.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 50.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 70.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

# NSN 5935-00-234-6615

Electrical Receptacle Connector - Page 2 of 2



habulan	Contact	Quantity:
ıncıuaea	Contact	Quantity:

24 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material:** 

Gold and silver

#### **Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0