NSN 5935-00-234-7527

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-234-7527

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling w/backshell |
| Overall Length: |
| 1.970 inches |
| Overall Diameter: |
| 1.370 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 120.0 and 240.0 and 300.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Thread Length: |
| 0.440 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 1.125 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber silicone class q single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| |

Solder well single mating end single contact grouping

NSN 5935-00-234-7527Electrical Plug Connector - Page 2 of 2



| Shell Material: |
|--|
| Plastic epoxy |
| Shell Material Specification: |
| Mil-p-18177, grade g-10 military specification single material response or mil-m-24325 military specification single material response |
| Included Contact Quantity: |
| 7 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.007 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |
| |