NSN 5935-00-235-2866

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-235-2866

Body Style:
Straight shape, flush mount
Overall Length:
0.954 inches
Overall Height:
3.110 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.782 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.125 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
67 all mating ends
Contact Removability:
Removable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Screw lock pin
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings and silver all mating ends all contact groupings
Insert Material:
Plastic all mating ends
Terminal Type:
Crimp all mating ends all contact groupings
Guide Design And Location:
Hexagon shape female post left-hand top at 5 oclock and hexagon shape female post right-hand top at 5 oclock

NSN 5935-00-235-2866

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Type:
Round pin all mating ends all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.067 gold grains, troy and 0.067 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0