## NSN 5935-00-235-5673

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-235-5673

**Body Style:** Right angle type **Overall Length:** 2.719 inches **Body Height:** 0.719 inches **Unthreaded Mounting Hole Diameter:** 0.170 inches **Distance Between Mounting Facility Centers:** 2.375 inches **Mating End Quantity: Contact Position Arrangement Style:** 17 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 725.0 single mating end single contact grouping **Polarization Method:** Shell Shell Type: Solid **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** Aluminum alloy **Insert Material Specification:** Mil-m-14, type mdg military specification single material response single mating end **Included Contact Quantity:** 17 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping

## NSN 5935-00-235-5673

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.017 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.