Electrical Receptacle Connector - Page 1 of 2



contact grouping

View Online at https://aerobasegroup.com/nsn/5935-00-236-2172

view Online at https://aeiobasegroup.com/hsi//3935-00-230-2172
Overall Length:
0.940 inches
Overall Height:
0.497 inches
Overall Width:
0.245 inches
Unthreaded Mounting Hole Diameter:
0.078 inches
Distance Between Mounting Facility Centers:
0.800 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a, spring federal specification single material response single mating end single cont
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Hermaphrodite single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.006 gold grains, troy
Precious Material:
Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.