

View Online at https://aerobasegroup.com/nsn/5935-00-236-2183

Plastic Fabrication Method: Molded Mounting Hole Diameter: 0.156 inches Body Mounting Hole Accommodation Diameter: 1.015 inches Distance Between Mounting Facility Centers: 1.406 inches Mounting Hole Style: Round, w/two mounting holes Specific Equipment Accommodated:
Molded Mounting Hole Diameter: 0.156 inches Body Mounting Hole Accommodation Diameter: 1.015 inches Distance Between Mounting Facility Centers: 1.406 inches Mounting Hole Style: Round, w/two mounting holes
Mounting Hole Diameter: 0.156 inches Body Mounting Hole Accommodation Diameter: 1.015 inches Distance Between Mounting Facility Centers: 1.406 inches Mounting Hole Style: Round, w/two mounting holes
0.156 inches Body Mounting Hole Accommodation Diameter: 1.015 inches Distance Between Mounting Facility Centers: 1.406 inches Mounting Hole Style: Round, w/two mounting holes
Body Mounting Hole Accommodation Diameter: 1.015 inches Distance Between Mounting Facility Centers: 1.406 inches Mounting Hole Style: Round, w/two mounting holes
1.015 inches Distance Between Mounting Facility Centers: 1.406 inches Mounting Hole Style: Round, w/two mounting holes
Distance Between Mounting Facility Centers: 1.406 inches Mounting Hole Style: Round, w/two mounting holes
1.406 inches Mounting Hole Style: Round, w/two mounting holes
Mounting Hole Style: Round, w/two mounting holes
Round, w/two mounting holes
-
Specific Equipment Accommodated:
Electron tube
Contact Material:
Copper alloy
Contact Surface Treatment:
Gold
Accommodated Contact Quantity:
20
Mounting Method:
Saddle
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Terminal Type And Quantity:
20 solder well
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02300