

View Online at <https://aerobasegroup.com/nsn/5935-00-236-2194>

**Overall Length:**

2.270 inches

**Overall Height:**

0.607 inches

**Overall Width:**

Between 0.521 inches and 0.541 inches

**Environmental Protection:**

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.128 inches

**Distance Between Mounting Facility Centers:**

Between 2.285 inches and 2.315 inches

**Board Accommodated Width:**

Between 0.086 inches and 0.103 inches

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Inter-contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder stud single mating end single contact grouping

**Included Contact Quantity:**

17 single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.017 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-21097/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.