## NSN 5935-00-236-4620

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-236-4620 **Thread Class:** 2b **Thread Direction:** Left-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.938 inches **Overall Height:** 1.688 inches **Overall Width:** 1.688 inches **Unthreaded Mounting Hole Diameter:** 0.169 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.282 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.282 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sk-m10 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 30.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded shell Thready Qty Per Inch (tpi): 6 **Thread Size:** 1.375 inches

**Terminal Location:** 

Back single mating end all contact groupings

## NSN 5935-00-236-4620

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Silver single mating end all contact groupings
Insert Material:
Plastic melamine single mating end or plastic phenolic single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
8 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Fireproof
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.010 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0