

View Online at <https://aerobasegroup.com/nsn/5935-00-236-5453>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.578 inches and 1.608 inches

Overall Diameter:

Between 0.557 inches and 0.567 inches

Distance From Mounting Shoulder To Front Face:

Between 0.651 inches and 0.661 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Sm 2nd mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

36 and 24 and 32

Thread Size:

0.250 inches and 0.625 inches and 0.313 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Material Specification:

Qq-b-626, comp 22, 1/2 @h federal specification single material response all mating ends all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response

Included Contact Quantity:

2 all mating ends all contact groupings

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends all contact groupings

Precious Material And Location:

Contact surfaces gold and shell surfaces silver

Precious Material And Weight:

0.010 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Uns and unef and unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0