NSN 5935-00-236-6203

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-236-6203 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.961 inches **Overall Diameter:** 1.641 inches **Distance From Mounting Shoulder To Front Face:** Between 0.691 inches and 0.722 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 45.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate

Included Contact Quantity:

19 single mating end single contact grouping

NSN 5935-00-236-6203

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0