Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-236-6248

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling w/backshell	
Overall Length:	
2.250 inches	
Overall Height:	
2.030 inches	
Overall Width:	
2.030 inches	
Environmental Protection:	
Moisture resistant and salt water resistant and vibration resistant	
Unthreaded Mounting Hole Diameter:	
0.147 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
1.562 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
1.562 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
22-55 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Key, multiple key groove	
Insert Position In Deg:	
218.0	
Shell Type:	
Solid	
Connector Locking Method:	
Externally threaded shell	
Thready Qty Per Inch (tpi):	
10	
Thread Size:	
1.750 inches	
Terminal Location:	
Back single mating end single contact grouping	



Contact Ma	
	v single mating end single contact grouping
	rface Treatment:
	mating end single contact grouping
Insert Mater	
-	I phthalate single mating end
Terminal Ty	
	e mating end single contact grouping
Shell Materi	ial:
Aluminum al	loy
Shell Surfac	ce Treatment:
Cadmium	
insert Mater	rial Specification:
Mil-m-19833	s, ty gdi-30f military specification single material response single mating end
included Co	ontact Quantity:
48 single ma	ating end single contact grouping
Included Co	ontact Type:
Round socke	et single mating end single contact grouping
Precious Ma	aterial And Location:
Contact surf	ace gold
Precious Ma	aterial And Weight:
0.048 gold g	rains, troy
Precious Ma	aterial:
Gold	
Thread Seri	es Designator:
Double stub	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	ition:
No	
Fiig:	
A039b0	
Mil-std (mili	itary Standard):
Mil-m-19833	spec.