Electrical Plug Connector - Page 1 of 2

AeroBase

View Online at https://aerobasegroup.com/nsn/5935-00-236-7943

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 0.923 inches and 0.947 inches
Overall Diameter:
0.875 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14s-2 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
20
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, gr b military specification 1st treatment response single mating end single contact

Mil-g-45204, type 1, gr b military specification 1st treatment response single mating end single contact grouping and qq-n-290, c1 1, grade b federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

NSN 5935-00-236-7943

Electrical Plug Connector - Page 2 of 2



Shell Material: Steel **Shell Surface Treatment:** Copper and cadmium and tin **Shell Surface Treatment Specification:** Mil-c-14550 military specification 1st treatment response and qq-p-416 federal specification 2nd treatment response and mil-t-10727 military specification 3rd treatment response **Shell Material Specification:** Qq-s-637 federal specification single material response **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.