## NSN 5935-00-237-3964

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-237-3964 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.562 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.484 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 2 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 15.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.375 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-00-237-3964

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Cardboard single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Flat socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0