## NSN 5935-00-237-4881

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-237-4881

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

Between 3.193 inches and 3.213 inches

**Overall Height:** 

Between 0.426 inches and 0.446 inches

**Overall Width:** 

Between 0.335 inches and 0.345 inches

**Environmental Protection:** 

Moisture proof and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.120 inches and 0.130 inches

**Distance Between Mounting Facility Centers:** 

Between 2.938 inches and 2.952 inches

**Board Accommodated Length:** 

2.493 inches single board and 2.507 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.071 inches

**Mating End Quantity:** 

1

## **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-750 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-19833, type gdi-30 military specification single material response single mating end

**Included Contact Quantity:** 

30 single mating end single contact grouping

## NSN 5935-00-237-4881

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Bifurcated spring single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.