

View Online at <https://aerobasegroup.com/nsn/5935-00-238-0300>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.375 inches

**Overall Diameter:**

1.375 inches

**Environmental Protection:**

Pressure proof and moisture resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"18-8, 22-404" single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

259.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber silicone class q single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

8 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact @surfaces gold

**Precious Material And Weight:**

0.008 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.