## NSN 5935-00-238-0663

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-238-0663

**Body Style:** 

Straight shape

**Overall Length:** 

1.869 inches

**Overall Height:** 

Between 0.368 inches and 0.372 inches

Overall Width:

0.275 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.138 inches and 0.142 inches

**Distance Between Mounting Facility Centers:** 

Between 1.590 inches and 1.598 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg military specification single material response single mating end

**Included Contact Quantity:** 

45 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-00-238-0663

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.045 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.