

View Online at <https://aerobasegroup.com/nsn/5935-00-238-4723>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/cable clamp

**Overall Length:**

1.437 inches

**Bushing Diameter:**

0.250 inches

**Overall Height:**

0.500 inches

**Overall Width:**

0.500 inches

**Environmental Protection:**

Pressure proof

**Unthreaded Mounting Hole Diameter:**

0.102 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.340 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.340 inches

**Cable Entrance Diameter:**

0.182 inches

**Distance From Mounting Shoulder To Front Face:**

0.310 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 single mating end

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

12400.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thread Length:**

0.115 inches

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Front single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530, comp a federal specification single material response single mating end single contact grouping

**Shell Material:**

Steel comp 303

**Shell Surface Treatment:**

Passivate

**Shell Material Specification:**

Qq-s-763, class 303 assn standard single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.