NSN 5935-00-238-8848

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-238-8848 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape center screwlock **Overall Length:** 2.625 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.387 inches **Overall Height:** 0.866 inches **Overall Width:** 0.564 inches **Environmental Protection:** Corrosion resistant and vibration resistant and thermal shock resistant and hermetic **Unthreaded Mounting Hole Diameter:** 0.120 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 100 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel single mating end single contact grouping and iron alloy single mating end single contact grouping

NSN 5935-00-238-8848

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic silicone single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Tin and nickel
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0