## NSN 5935-00-238-9680

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-238-9680 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Diameter:** 1.250 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** 

Silver

## NSN 5935-00-238-9680

Electrical Plug Connector - Page 2 of 2



| Included Contact Quantity:     |
|--------------------------------|
| 1 single mating end single cor |

ntact grouping

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact and body surfaces silver

**Precious Material And Weight:** 

0.105 silver grains, troy

**Precious Material:** 

Silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0