NSN 5935-00-239-9637

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-239-9637

Body Style:
Hood, side opening w/clamp
Overall Length:
2.040 inches
Overall Height:
2.390 inches
Overall Width:
0.670 inches
Cable Entrance Diameter:
0.375 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
26 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Jackscrew Shell Type:
Shell Type:
Shell Type: Hood, side opening
Shell Type: Hood, side opening Connector Locking Method:
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method:
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type:
Shell Type: Hood, side opening Connector Locking Method: Jackscrew-socket Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type: Crimp single mating end single contact grouping

Anodize

NSN 5935-00-239-9637

Electrical Plug Connector - Page 2 of 2



Shell	Surface	Treatment	Specification	n:
OHEH	Juliace	HEALINGIL	Obecilication	

Mil-a-8625, type 1 military specification single treatment response

Shell Material Specification:

Qq-a-250/8, alloy 5052, h32 federal specification single material response

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

10001-2655533 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

	Lif	

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-a-8625 spec.