
NSN 5935-00-240-1306

Tip Jack - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Brown **Body Style:** Threaded bushing mounted **Overall Length:** 0.906 inches Mounting Bushing Length: 0.469 inches **Body Length:** 0.657 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round w/double flat Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Banana spring single finger **Finger Accommodation Diameter:** 0.163 inches single finger Finger Accommodation Length: 0.657 inches single finger **Bushing Thru-hole Accommodation Length:** 0.250 inches **Bushing Thru-hole Accommodation Width:** 0.313 inches **Capacitance In Picofarads:** 5.5 **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing **Thread Size:** 0.312 inches **Terminal Type:** Tab, solder lug

NSN 5935-00-240-1306

Tip Jack - Page 2 of 2

Material:

Plastic, polyamide cap

Material:

Plastic polyamide cap

Surface Treatment:

Cadmium terminal

Surface Treatment:

Cadmium terminal

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400

