Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-240-2113

| View Online at https://aerobasegroup.com/nsn/5935-00-240-2113 |
|--|
| Overall Length: |
| 1.640 inches |
| Overall Height: |
| 0.590 inches |
| Overall Width: |
| 0.245 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.078 inches |
| Distance Between Mounting Facility Centers: |
| 1.500 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Contact Material Specification: |
| Qq-b-750, comp a spring federal specification single material response single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-14, type sdg-f military specification single material response single mating end |
| Included Contact Quantity: |
| 20 single mating end single contact grouping |
| Included Contact Type: |
| Hermaphrodite single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.020 gold grains, troy |
| Precious Material: |

Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.