NSN 5935-00-240-2120

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-240-2120

Body Style:
Straight type
Overall Length:
3.156 inches
Overall Height:
0.656 inches
Overall Width:
0.219 inches
Unthreaded Mounting Hole Diameter:
0.078 inches
Distance Between Mounting Facility Centers:
3.031 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Contact
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Bracket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder stud single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a spring federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

NSN 5935-00-240-2120

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.