NSN 5935-00-240-2504

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-240-2504

view Offilite at https://aerobasegroup.com/hist//0300-00-240-2004
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.370 inches
Overall Height:
1.360 inches
Overall Width:
0.560 inches
Environmental Protection:
Vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.138 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 2 class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 class 2
federal specification 2nd treatment response single mating end single contact grouping

Solder well single mating end single contact grouping

Terminal Type:

NSN 5935-00-240-2504

Electrical Plug Connector - Page 2 of 2



Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize and dichromate potassium
Shell Material Specification:
Qq-a-250 federal specification single material response
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.