NSN 5935-00-240-2999

Electrical Receptacle Connector Body - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-240-2999 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Rectangular shape, w/jackscrew |
| Overall Length: |
| Between 2.410 inches and 2.430 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 2.035 inches and 2.055 inches |
| Overall Height: |
| 3.400 inches |
| Overall Width: |
| Between 1.340 inches and 1.360 inches |
| Environmental Protection: |
| Thermal shock resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.149 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.802 inches and 0.822 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 80 single mating end |
| Polarization Method: |
| Polarization boss |
| Connector Locking Method: |
| Jackscrew |
| Operating Tempurature Rating: |
| Between -54.0 degrees celsius and 125.0 degrees celsius |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Insert Material: |
| Plastic diallyl phthalate glass filled single mating end |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification single material response single mating end |

Unf

Thread Series Designator:

NSN 5935-00-240-2999

Electrical Receptacle Connector Body - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |

Mil-std (military Standard):

Mil-m-14 spec.

Shelf Life: