

View Online at <https://aerobasegroup.com/nsn/5935-00-240-7542>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.400 inches

Overall Diameter:

1.078 inches

Environmental Protection:

Pressure proof and dripproof and shock proof and vibration resistant

Distance From Mounting Shoulder To Front Face:

Between 0.681 inches and 0.701 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.187 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

8-4 all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Size:

0.563 inches

Contact Surface Treatment:

Gold all mating ends all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

Shell Material:

Steel

Included Contact Quantity:

4 1st mating end all contact groupings

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round socket 2nd mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.